

Technical Documentation

SEAL-IT® 560 PANELTAPE

Product

Seal-it® 560 PANELTAPE is a double-sided adhesive mounting tape. Specifically developed for Use in combination with panel glue to obtain extra initial adhesive strength and the correct adhesive thickness.

Applications

- Extremely suitable for fixing various plastic panels.
- For various applications in e.g., bodywork.

Properties

- Ensures the correct adhesive layer thickness.
- To be used on planed spruce, aluminium and/or galvanized steel.
- Adheres to most surfaces.
- Flexible so that small irregularities in the subsoil are absorbed.

Standard Range

Colour	Roll 12x3mm (25m)
Black	SI-560-312-2500

Shelf Life

In the unopened original packaging, store in a cool and dry place between +5°C and +25°C. Shelf life of up to 24 months after the date of production.

Application Conditions

- Seal-it® 560 PANELTAPE can be used for a correct attachment of (façade) panels.
- Seal-it® 560 PANELTAPE adheres directly to most surfaces.
- Apply vertically to battens and make sure the tape runs straight as much as possible.
- To be applied in the desired shape and length.
- Do not apply under tension.
- The tape is highly weather- and tear-resistant.

Safety and Health

The product safety data sheet should be read and is available on request.



Connect Products B.V.

Duurzaamheidsring 220
4231 EX Meerkerk
The Netherlands

info@connectproducts.nl
+31 (0)183 731 400
www.connectproducts.nl



Technical Documentation

SEAL-IT® 560 PANELTAPE

Warranty and Liability

Connect Products B.V. guarantees that its product, within the shelf life, is in accordance with the specifications. The liability will never exceed what is determined in our general terms and conditions of sale and delivery. In no case is the seller liable for any consequential damage. The information provided is the result of our tests and experience and is of a general nature. However, it does not imply any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.



Disclaimer

All information in our publications, both printed and digital, is the exclusive (intellectual) property of Connect Products B.V. and is based on our current knowledge and experience. Copying, showing to third parties or in any other way duplicating, publishing and/or using this document, including the findings herein, is only permitted with the express permission of Connect Products B.V. The technical data are indicative and not all-inclusive. Connect Products B.V. accepts no liability for damage, direct or indirect, resulting from any errors, incompleteness or inaccuracies in this document, including those resulting from technological changes or research between publication and obtaining the product. Connect Products reserves the right to make changes to formulations. Connect Products B.V. is not liable for any (direct or indirect) damage resulting from the use of the product shown in this document. Users must consult and understand all relevant information about our products before applying and using the product. The user is responsible for performing appropriate tests to ensure that the product is suitable for the intended application. Connect Products B.V. has no influence on the method of application of the product and the conditions during storage and transport and as a result accepts no liability for damage. Deliveries are made exclusively according to our general terms and conditions of delivery, as filed with the Chamber of Commerce.

Connect Products B.V.

Duurzaamheidsring 220
4231 EX Meerkkerk
The Netherlands

info@connectproducts.nl
+31 (0)183 731 400
www.connectproducts.nl

