

Declaration of Performance (DoP)
SEAL-IT® 230 TOPFLEX-P



PV/LE/DoP-Nr. 230-003

1. Identification of product type: Seal-it® 230 TOPFLEX-P
2. Identification no.: See product packaging for batch number
3. Designated use: 1 component silicon sealant, neutral curing
Sealant for façade elements: Type F-EXT-INT-CC 25HM
Sealant for glazing: G-CC 25HM
4. Manufacturer: Connect Products BV
Duurzaamheidsring 220
Meerkerk, The Netherlands
5. Authorized representative: -
6. System for evaluating reliability of performance: 3 plus 3
7. Harmonized standard: EN 15651-1: 2012-12, EN15651-2:2012-12
8. Notified body: SKZ Testing GmbH (NB-nr. 1213) as notified body performed the initial type testing under system 3 and issued a test report.
9. Important characteristics:

Important characteristic	Performance	Harmonized technical specification
Fire behaviour	Class E	EN 15651 - 1: 2012-12 Conditioning: Procedure A Beton M1 without primer EN 15651 - 2: 2012-12 Conditioning: Procedure A Glass without primer
Release of hazardous chemicals to health and/or the environment	See MSDS	
Elastic recovery	≥ 60%	
Stability under load	≤ 3mm	
Tensile properties	> 0,6 MPa	
Volume loss	< 10%	
Elastic recovery	>70%	
Tensile properties at pre-tensioning	NF	
Adhesion/cohesion at pre-tensioning at variable temperatures	NF	
Adhesion/cohesion at pre-tensioning after water immersion	NF	
Adhesion/cohesion properties after exposure to heat water and artificial light	NF	
Durability	NF	NF = non failure / passed

10. The performance of the product as per number 1 and number 2 is conform to the performance as set out under number 9.

This declaration of performance is issued under the responsibility of the manufacturer identified in point 4.
Signed on behalf of the manufacturer:

Jan van 't Verlaat
Meerkerk, 06-08-2024