

Technical Documentation

SEAL-IT® 355 ROOFBOND-ALL

Product

SEAL-IT® 355 Roofbond-All is a 1-component high-quality professional strong adhesive adhesive on MS-Polymer® basis. Specifically for repair and sealing of roof and gutter leaks.

Applications

- Waterproof and flexible sealing and repair of roof and gutter leaks.
- For sealing penetrations, connections, overlaps of roof edges and skylights.
- Bonding shingles.
- Bonding corrugated sheets, skylights, skylights.
- Sealing the rainwater drainage system on the roof.

Properties

- Excellent adhesion without primer on practically all and even damp surfaces.
- Ideal for bituminous substrates.
- Permanently plasto-elastic.
- Solvent-free.
- Durable.
- Easy to use.
- Contains no harmful ingredients.



Standard Range

Colour	12 x 290ml tube
Black	SI-355-9100-290

Other colours and/or packaging on request.

Technical Product Data

PROPERTY	STANDARD	SPECIFICATION
Basis		MS-POLYMER® 1-COMPONENT
Standardity	ISO 7390	<2mm
Density		1,25g/ml
Skin formation time	+23°C/50% RV	>15 hours
Solid matter content		>99%
Temperature resistance after complete curing		-40/+100°C
Shrinkage		None

Shelf life

In unopened original packaging, store in a cool and dry place, between +5°C and +25°C. Shelf life of up to 15 months after production date.

Connect Products B.V.

Duurzaamheidsring 220
4231 EX Meerkkerk
The Netherlands

info@connectproducts.nl
+31 (0)183 731 400
www.connectproducts.nl



SEAL-IT® 355 ROOFBOND-ALL

Application Conditions

- Processing temperature (environment and substrate) between min. +5°C and max. +40°C.
- On load-bearing, compatible, clean, grease- and dust-free surfaces.
- Completely remove loose components from substrates using a suitable brush.
- Degrease surfaces well using Seal-it® 510 CLEANER.
- Always test in advance for adhesion to the substrate.

Restrictions and Recommendations

Unsuitable for PTFE substrates. Always ensure sufficient humidity from the immediate environment/subsoil during curing. Do not mechanically, thermally and chemically load, for complete curing. Repair with the same material. Adhesive sealants function more sustainably if structural maintenance and timely repair are carried out. Always test adhesion and material compatibility beforehand.

Cleaning

Remove fresh, uncured and/or excess material from surfaces and tools using water. Clean hands/skin using SEAL-IT® 515 ULTRA-WIPES or soapy water. Cured material can only be removed mechanically using the correct tools.

Safety and Health

Avoid prolonged skin contact. If uncured material comes into contact with eyes, rinse immediately with water and seek medical advice. Safety data sheet available on request.

Warranty and Liability

Connect Products B.V. guarantees that its product, within the shelf life, is in accordance with the specifications. The liability will never exceed what is determined in our general terms and conditions of sale and delivery. In no case is the seller liable for any consequential damage. The information provided is the result of our tests and experience and is of a general nature. However, it does not imply any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.



Connect Products B.V.

Duurzaamheidsring 220
4231 EX Meerkerk
The Netherlands

info@connectproducts.nl
+31 (0)183 731 400
www.connectproducts.nl



SEAL-IT® 355 ROOFBOND-ALL



Disclaimer

All information in our publications, both printed and digital, is the exclusive (intellectual) property of Connect Products B.V. and is based on our current knowledge and experience. Copying, showing to third parties or in any other way duplicating, publishing and/or using this document, including the findings herein, is only permitted with the express permission of Connect Products B.V. The technical data are indicative and not all-inclusive. Connect Products B.V. accepts no liability for damage, direct or indirect, resulting from any errors, incompleteness or inaccuracies in this document, including those resulting from technological changes or research between publication and obtaining the product. Connect Products reserves the right to make changes to formulations. Connect Products B.V. is not liable for any (direct or indirect) damage resulting from the use of the product shown in this document. Users must consult and understand all relevant information about our products before applying and using the product. The user is responsible for performing appropriate tests to ensure that the product is suitable for the intended application. Connect Products B.V. has no influence on the method of application of the product and the conditions during storage and transport and as a result accepts no liability for damage. Deliveries are made exclusively according to our general terms and conditions of delivery, as filed with the Chamber of Commerce.

Connect Products B.V.

Duurzaamheidsring 220
4231 EX Meerkkerk
The Netherlands

info@connectproducts.nl
+31 (0)183 731 400
www.connectproducts.nl

