

Declaration of Performance (DoP)
SEAL-IT® 318 FACADE-PLUS



PV/LE/DoP-Nr. 318-002

1. Identification of product type: **Seal-it® 318 FAÇADE-PLUS**
2. Identification no.: **See product packaging for batch number**
3. Designated use: **1-component hybrid polymer sealant, neutral curing.
Sealant for façade elements: Type F-EXT-INT-CC 25HM**
4. Manufacturer: **Connect Products BV
Duurzaamheidsring 220
Meerkerk, The Netherlands**
5. Authorized representative: **-**
6. System for evaluating reliability of performance: **3 plus 3**
7. Harmonized standard: **EN 15651-1: 2017-07**
8. Notified body: **SKZ Testing GmbH (NB-nr. 1213) as notified body performed the initial type testing under system 3 and issued a test report.**
9. Important characteristics:

Important characteristic	Performance	Harmonized technical specification
Fire behaviour	Class E	EN 15651 - 1: 2017-07 Conditioning: Procedure B Beton M1 with primer
Release of hazardous chemicals to health and/or the environment	See MSDS	
Stability under load	< 3mm	
Tensile properties	> 0,6 MPa	
Volume loss	< 5%	
Tensile properties at pre-tensioning in a cold climate (-30°C)	NF	
Adhesion/cohesion at pre-tensioning after water immersion	NF	NF = non failure / passed
Durability	NF	

10. The performance of the product as per number 1 and number 2 is conform to the performance as set out under number 9.

This declaration of performance is issued under the responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Jan van 't Verlaat
Meerkerk, 07-12-2023