

Declaration of Performance (DoP)

SEAL-IT® 352 SUPER-PRO



PV/LE/DoP-Nr. 352-002

1. Identification of product type: Seal-it® 352 SUPER-PRO
2. Identification no.: See product packaging for batch code
3. Designated use: 1-component hybrid polymer sealant,
Neutral curing.
Sealant for application in facade: Type F-INT
4. Manufacturer: Connect Products BV
Duurzaamheidsring 220
Meerkerk, The Netherlands
5. Authorized representative: -
6. System for evaluating reliability of performance: 4 plus 3
7. Harmonized standard: EN 15651-1: 2012-12
8. Notified body: IFT Rosenheim (NB-nr. 0757) – Reaction to fire
9. Important characteristics:

Important characteristic	Performance	Harmonized technical specification
Fire behaviour	Class E	EN 15651-1: 2012-12 Conditioning: Method A Aluminium
Release of hazardous chemicals to health and/or the environment	Evaluated	
Stability under load	≤ 3mm	
Volume loss	≤ 45%	
Tensile properties at 23°C	≥ 25%	
Tear resistance	NF	
Durability	NF	NF = non failure / passed

10. The performance of the product as per number 1 and number 2 is conform to the performance as set out under number 9.

This declaration of performance is issued under the responsibility of the manufacturer identified in point 4.
Signed on behalf of the manufacturer:

Jan van 't Verlaat
Meerkerk, 29-11-2017