

Declaration of Performance (DoP)
SEAL-IT® 353 SUPER-STRONG



PV/LE/DoP-Nr. 353-003

1. Identification of product type: Seal-it® 353 SUPER-STRONG
2. Identification no.: See product packaging for batch code
3. Designated use: 1-component hybrid polymer sealant,
Neutral curing.
Sealant for application in facade: Type F-EXT-INT-CC 20HM
Sealant used for sanitary application: XS3
Sealant used for pedestrian walkways: EXT-INT-CC 20HM
4. Manufacturer: Connect Products BV
Duurzaamheidsring 220
Meerkerk, The Netherlands
5. Authorized representative: -
6. System for evaluating reliability of performance: 3 plus 3
7. Harmonized standard: EN 15651-1: 2012-12, EN 15651-3: 2012-12, EN 15651-4: 2012-12
8. Notified body: ITC (NB-nr. 1023)
9. Important characteristics:

Important characteristic	Performance	Harmonized technical specification
Fire behaviour	Class E	EN 15651-1: 2012-12 Conditioning: Method B Substrate: Aluminium
Release of hazardous chemicals to health and/or the environment	Evaluated	
Water- and airtightness		
a) Stability under load	≤ 3mm	
b) Volume loss	≤ 5%	
c) Elastic recovery	≥ 60%	
d) Tensile properties at 23°C	≥ 0,4 MPa	
e) Tensile properties in cold climate (-30°C)	≥ 0,6 MPa	
f) Tensile properties at pre-tensioning in a cold climate (-30°C)	NF	
g) Tensile properties at pre-tensioning at variable temperatures	NF	
h) Tensile properties at pre-tensioning after water immersion	NF	
Durability	NF	EN 15651-3: 2012-12 Conditioning: Method B Substrate: Aluminium
Microbiological growth	3	
Tear resistance	NF	EN 15651-4: 2012-12 Conditioning: Method B Substrate: Aluminium
		NF = non failure / passed

10. The performance of the product as per number 1 and number 2 is conform to the performance as set out under number 9.

This declaration of performance is issued under the responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Jan van 't Verlaat
Meerkerk, 24-10-2024