

Declaration of Performance (DoP)

SEAL-IT® 326 GLAZING



PV/LE/DoP-Nr. 326-001

1. Identification of product type: Seal-it® 326 GLAZING
2. Identification no.: See product packaging for batch number
3. Designated use: 1-component hybrid polymer sealant, neutral curing.
Sealant for glazing: G-CC-20HM
Sealant for use in facades: F-EX-INT-20HM (pending)
4. Manufacturer: Connect Products BV
Duurzaamheidsring 220
Meerkerk, The Netherlands
5. Authorized representative: -
6. System for evaluating reliability of performance: 3 plus 3
7. Harmonized standard: EN 15651-1: 2012-09
8. Notified body: SKZ Testing GmbH (NB-nr. 1213) as notified body performed the initial type testing under system 3 and issued a test report.

9. Important characteristics:

Important characteristic	Performance	Harmonized technical specification
Fire behaviour	Class E	EN 15651 - 1: 2012-09 Conditioning: Procedure B Glass without primer
Release of hazardous chemicals to health and/or the environment	Evaluated	
Water and airtightness		
Elastic recovery	> 60%	
Volume loss	< 3,1%	
Stability under load	< 3mm	
Tensile properties	> 0,4 MPa	
Tensile properties at pre-tensioning	NF	
Tensile properties at pre-tensioning in a cold climate (-30°C)	NF	
Tensile properties at pre-tensioning at variable temperatures	NF	
Adhesion/cohesion at pre-tensioning after water immersion	NF	
Adhesion/cohesion after exposure to heat, water, and artificial light	NF	
Durability	NF	
		NF = non failure / passed

10. The performance of the product as per number 1 and number 2 is conform to the performance as set out under number 9.

This declaration of performance is issued under the responsibility of the manufacturer identified in point 4.
Signed on behalf of the manufacturer:

Jan van 't Verlaat
Meerkerk, 23-06-2026